



AG-PANEL

AG -Panel is the most economical roofing exposed fastener panel. Available Materials: Aluminum, Copper, Corten/A606-4, Steel Available Finishes: Bare Steel, Galvalume®/Zincalume®, Galvanized, PVDF, SMP Painted



SPECIFICATIONS:

Profile Type:	AG Panel
Rib Height:	3/4′
Rib Distance (Pitch):	9′
Overall Width:	36'
Coil Feed:	41′
Warranty:	40 year limited*
Coverage Area	

Roof: 36" Wall: 36" **Available Gauges:** 29, 26, 24 Substrate: AZ 50 Minimum (Galvalume®/Zincalume®) Finish: CT-SMP (Cool Tech - SMP) **Fasteners: Exposed**

Panel Length: Recommended Minimum Roof Slope:

Installation: Can be installed over an open purlin system

or a solid substrate. Use bead mastic on the overlap if used for a roofing application.

TESTING AND APPROVALS:

For the complete list, please contact your sales representative

- · ASTM A653 G90 Galvanized
- ASTM A792 Zincalume/Galvalume AZ-50/55
- ASTM B209 Aluminum Substrate

APPLIES TO THE FOLLOWING COLORS/FINISHES:

- Antique Rustic®
- Country Red
- Polar White
- Desert Beige
- Light Stone

• Light Gray

- Emerald Green · Koko Brown
- Sahara Tan
- Steel Gray

PROFILE:



1' to 45'

3/12

Colors represented on this profile sheet may not match actual material. All colors should be verified using an actual metal color sample.

^{*}Limited warranty. Please review prior to purchase.