## SHARKSKIN



All construction professionals know the importance of a quality roof system. That is why so much research, time and effort goes into specifying and installing the right roofing product for every building.

The SHARKSKIN COMP® is designed to ensure that quality asphalt shingle and metal roof installations are not short-changed by inferior 'old-technology' asphalt felts. The state-of-theart in recent synthetic roof underlayment advances, SHARKSKIN COMP® is 100% polypropylene product with a 6 month UV exposure rating. It is a tough nailable polymer underlayment. Now for use under metal roof applications. See label instructions.

Thermally stable with a melting point of 320° F, this wind resistant, reinforced product is approved as an alternate to inferior Type 15 and Type 30 roofing felts.

These days you can't afford to open yourself up to the potential liability of inferior roof underlayments. Give your customers a superior roofing system by starting with "The Ultimate Roof Underlayment".

Specify Sharkskin Comp®.



Developed to exceed industry standards for long term moisture protection!

# **Code Compliance**

- ICC AC188
- ESR Report 1708
- BOCA
- SBCCI
- Florida Building Code FL#8087 R-4
- Miami/Dade HVHZ NOA 15-0421.10
- Exceeds ASTM D226

Kirsch Building Products LLC
Tel: (877) 742-7507
Fax: (805) 526-1116
email: kirsch@sharkskin.us
www.sharkskin.us

1464 Madera Road #N Suite 387 Simi Valley, CA 93065

Patent # 6,308,482 American Owned and Operated 100% Recyclable 101-12004







**Engineered to exceed** 

industry standards for

long term moisture

protection!

# Benefits

#### Fantastic Wind Resistance

Helps eliminate blow-off

## White/Grey Surface

Stays cool to work on and keeps buildings cooler during construction

#### Slip-Resistant

Even in wet or dusty conditions

# No Expansion/Contraction

Material remains stable

## Improved Fastening

Installs with Standard EG Roofing Nails\* and Hammer Tacker Staples\*

#### Will Not Wrinkle

Does not absorb moisture

#### Will Not Scar or Melt

NO Sticky Mess Withstands high temperatures

#### Will Not Rot

Will not rot, dry out or become brittle

## Provides Secondary Water Barrier Protection

Against high winds and haif

## Printed Lay-Line System

Improves shingle installation FatentPending

### Light Weight

Easy to lift, load, and work with 48" x 250" 38 lbs. per roll approx.

\* Must be installed per manufactures printed installation labels on each roll.

Visit Our Website! www.sharkskin.us



The first and most important step toward an integrated roof system.

